

| (Specification)     | (Details)                                              |
|---------------------|--------------------------------------------------------|
| Amplifier type      | Dual class D                                           |
| Power output        | 30W RMS per channel, AES                               |
| Drivers             | 3.5" woofer, 1" silk dome tweeter                      |
| Inputs              | 1/8" (3.5 mm) stereo, 1/4" stereo, RCA, USB, Bluetooth |
| Outputs             | RCA Sub-out, 1/8" (3.5 mm) headphone out               |
| Mains voltages      | 100-240 V, 50/60 Hz auto-switching                     |
| SNR                 | >85 dB (typical A-weighted)                            |
| THD+N               | <0.05% at all power settings                           |
| Crosstalk           | <60 dB                                                 |
| Frequency response  | 68 Hz – 22 kHz $\pm$ 2.0 dB                            |
| Input impedance     | 10K ohms unbalanced                                    |
| Protection          | Output current limiting, thermal, transient protection |
| Connector type      | TYPE-C USB audio                                       |
| Internal D/A & BT   | BT8961 (Bluetooth 5.4)                                 |
| Input bit depth     | up to 24 bits native                                   |
| Input sample rate   | up to 96KHz native                                     |
| Dimensions (each)   | 9.45" (H) x 5.51" (W) x 6.89" (D)                      |
| Weight (Left/Right) | 2.26 Kg / 1.87 Kg                                      |